

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Box PATENT APPLICATION
ASSISTANT COMMISSIONER FOR PATENTS
Washington, D.C. 20231

Transmitted herewith for filing is the patent application of:
Inventors: C Stuart Johnson, Greg W. Davis and Timothy S. Michels
For: SWITCHING DEVICE WITH MULTISTAGE QUEUING SCHEME

Enclosed are:

- [X] 10 pages of specification, 3 pages of claims, an abstract and an unsigned Combined Declaration and Power of Attorney.
[X] 2 sheet(s) of ~~format~~ drawings.
[X] Information Disclosure Statement Form PTO-1449 and references

CLAIMS AS FILED					
For	Number Filed		Number Extra	Rate	Basic Fee \$395.00
Total claims	21	-20	1	x \$11.00 =	11.00
Independent Claims	3	-3	0	x \$41.00 =	0.00
TOTAL FILING FEE					\$406.00

DATE OF DEPOSIT: October 5, 1998

One World Trade Center, Suite 1600
121 S.W. Salmon Street
Portland, Oregon 97204
Telephone: (503) 226-7391

cc: Yvonne McDonald
Docketing Secretary

Respectfully submitted,

KLARQUIST SPARKMAN CAMPBELL
LEIGH & WHINSTON, LLP

By 

Mark L. Becker
Registration No. 31,325

SWITCHING DEVICE WITH MULTISTAGE QUEUING SCHEME

TECHNICAL FIELD

5 This invention relates generally to network switching devices. More particularly, this invention relates to a method and means for forwarding data packets through a switching device.

BACKGROUND OF THE INVENTION

10 A local area network (LAN) is a system for directly connecting multiple computers so that they can directly exchange information with each other. LANs are considered local because they are designed to connect computers over a small area, such as an office, a building, or a small campus. LANs are considered systems because they are made up of several components, such as cables,
15 repeaters, switches, routers, network interfaces, nodes (e.g., computers), and communication protocols. Ethernet is one such protocol. Information is communicated through a LAN in frames transported within data packets. ("Frame" and "data packet," while technically different, are often used interchangeably to describe data carrying the information.)
20 A LAN switch (or, more generally, a packet switch) is generally defined as a multi-port device that transfers data between its different ports based on the destination addresses and/or other information found in the individual packets it receives. Switches can be used to segment LANs, connect different LANs, or extend the collision diameter of LANs. Switches are of particular importance to
25 Ethernet-based LANs because of their ability to increase network diameter. Additional background information on packet switches can be found in a number of references such as *Fast Ethernet* (1997) by L. Quinn et al., *Computer Networks* (3rd Ed. 1996) by A. Tannenbaum, and *High-Speed Networking with LAN Switches* (1997) by G. Held, all of which are incorporated herein by reference.
30 Packet switches generally carry three types of traffic: unicast, multicast and broadcast. Unicast traffic consists of packets that travel from a source, or entry, port to a single destination, or exit, port. Multicast traffic consists of packets that

travel from one sending port to many destination ports per a destination list within a packet. Broadcast traffic is a special case of multicast traffic wherein the destination list includes all destination ports, and as such issues surrounding multicast apply equally to broadcast traffic.

5 Multicast traffic poses a problem for packet switches because multicast packets must be replicated within the packet switch. This replication can cause packet switches to fall behind in transmitting frames that follow the multicast frame due to the time required for replication. This replication time is particularly apparent in crossbar switch architectures that require unimpeded access from the
10 sending port to the destination ports to schedule transmission, as the sending port must wait for other traffic that is destined for the destination port to complete. Shared memory switch architectures do not suffer the same fate as all ports have access to the switch memory independent of each other. In shared memory switches, a packet is stored in a central memory and the sending port makes a
15 forwarding decision that notifies the destination ports of the packet's location for transmit. Each destination port can pull a multicast packet from its storage location independent of the other ports. However, in shared memory switches, the response of the destination ports to the forwarding decision can be time-consuming where, for example, it involves a multicast packet. Each of the destination ports on the
20 destination list must request the packet from the shared memory. The time required for this delays further forwarding decisions and can cause congestion in the sending port if additional traffic is received there while the destination ports complete their requests.

Congestion in packet switches can be caused in many ways. In cases where
25 there is more than one port transmitting to a single destination port, congestion at the destination port can occur and the port is said to be oversubscribed. The ratio of the rate that traffic is generated at the sending ports to the rate the destination port can transmit is called the oversubscription ratio. Rate mismatches in the source network media and destination network media can also cause congestion
30 (another case of oversubscription). For example, if traffic travels from port 0 to port 1 on a switch and port 0 runs at 100 megabits per second and port 1 runs at 10 megabits per second, traffic can easily back up waiting to exit port 1. Traffic

shaping can also cause congestion. This is a process where the destination port is intentionally curbed back to a lower transmit rate than it is capable for traffic engineering purposes.

Normal packet network traffic does not allow steady state oversubscription.

- 5 No network switching equipment can buffer infinite data, so oversubscribed conditions on ports are inherently limited by the storage capabilities of the network equipment. However, it is also normal network behavior to have bursts for short periods of time during which network ports will be oversubscribed for any or all of the reasons previously listed. High port count switching equipment creates the
- 10 opportunity for high oversubscription ratios during these normal traffic bursts.

- End stations (such as a node within a LAN) communicate through a packet network by establishing a channel called a session. This session has characteristics that remain constant during the conversation between the end stations. For example, if station A talks to station B through the packet network to transfer a
- 15 file, when A sends packets, they are all labeled with B's network address as the destination, and A's network address as the source. Other information in the packets sent between A and B will also generally remain constant for a given session - priority, VLAN, network protocol, etc. Each station in a packet network may run multiple sessions with the same or different destination stations. In
- 20 general, packets within these sessions must arrive in sequence at their destinations - that is, the network equipment must not re-order them.

- As a packet from a given session enters a packet switch, the switch must evaluate fields within the packet and make a forwarding decision (where does the packet go?). After making a forwarding decision, packet switches with egress
- 25 queuing must place multicast packets on more than one transmit queue (a queue being first in/first out storage). As network media speeds increase, the time allowed to perform these queuing operations shrinks. Egress port congestion aggravates this issue. High oversubscription ratios that result from normal packet network operation force egress queuing mechanisms to queue packets from many
- 30 sources simultaneously to maintain predictable operation. The more work the queuing mechanism performs to handle congestion, the harder it is to perform multicast packet replication.

An objective of this invention, therefore, is to provide a method and means for enhancing the communication of packets, such a multicast packets, through a switching device.

5

SUMMARY OF THE INVENTION

In a switching device, a method of communicating data packets from sending ports to destination ports includes storing in a first stage queue packet-related data from a sending port; determining from the packet-related data which destination ports are to receive the packet-related data in the first stage queue; storing in a second stage queue associated with each determined destination port the packet-related data from the first stage queue; and using the packet-related data in the second stage queue to complete the communication of the data packet from the sending port to each determined destination port. Apparatus for practicing the method comprises a first stage queue storing packet-related data from a sending port; and a second stage queue associated with each of a set of destination ports storing the packet-related data from the first stage queue.

15

These and other aspects, features, and advantages of the invention are described in an illustrative embodiment below in conjunction with the following drawings.

20

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is an overall block diagram of a packet switch in accordance with the invention.

Fig. 2 is a block diagram of a queuing device within the packet switch of Fig. 1.

25

DETAILED DESCRIPTION OF AN ILLUSTRATIVE EMBODIMENT

Overview

As a session's packets travel through the packet network, they may take different paths to the same destination based on data field contents in their packets. For example, a video conference session between station A and B may be marked as priority 7, VLAN 5 while an email session between the same two stations may

30

be marked as priority 3, VLAN 12 even though the sessions have the same source and destination. As a result of these differences in the sessions, the packets in the data streams may take physically different routes through the network. The sessions may also take the same route through the network, but be serviced
5 differently by the network equipment - a packet from one session may come into a switch after a packet from a different session, yet exit the switch first as a result of higher priority servicing.

Network switches can examine these data fields in each packet to classify it. This invention takes advantage of packet classification to reduce the bandwidth
10 burden of queuing multicast packets during congested intervals. This is accomplished by identifying classifications (characteristics) of packets that are independent of whether a packet is unicast or multicast. By doing this, queuing can be broken up into stages such that the first stage is only concerned with a broad range of packet types (and potentially sessions) that are destined for any port in a
15 group of ports. Further stages can then service these queues as appropriate and perform additional queuing for multicast by replicating the packet for each destination port. The multicast replication still occurs within the switch, but is not required to occur immediately as the first stage of queuing acts as a buffer for the subsequent stages. This allows for the absorption of normal bursty
20 oversubscription conditions while maintaining session servicing consistency (packet ordering).

An example of this invention is a two stage queuing scheme whereby the first stage queues packets based solely on their priority. All sessions with a given priority are given equal weight in the first stage queue. Note that these include
25 multicast and unicast sessions. All packets within a session are placed in a single queue, thus maintaining packet ordering requirements. A second stage queue services or empties the priority queues into port queues, expanding multicast packets onto multiple queues if necessary. Since the first stage queues are not required to expand multicast packets onto multiple destination ports, fewer queuing
30 operations are required to queue the packets to their destinations in the first stage. Multicast replication is handled by second stage queuing mechanisms. This allows more ports to be effectively utilized in normal bursty oversubscribed packet

09166344-100698

network conditions due to rate mismatches, traffic shaping, oversubscription and port density. This is increasingly important as network media speeds achieve gigabit per second and beyond.

5 The operation of the illustrative embodiment is such that the multistage queuing is not visible except during congested intervals on ports receiving multicast traffic. That is, it is transparent during normal operation and operates as a performance enhancement during peak utilization.

10 Note that this invention is not limited to the use of priority as a first stage queuing criteria. This is an arbitrary session characteristic that was chosen as a classification rule, which could as easily have been network protocol type or type of service. Note also that this invention is not limited to egress queuing devices, and may have applications in ingress queuing packet switches. Nor is this invention limited to a two stage queuing pipeline.

15 *Structure and Function*

Fig. 1 is a block diagram of a portion of a switching device 18 in accordance with the invention. The switching device includes a number of bidirectional ports 20 (numbered individually as ports 1 through 10) each which includes a media access control (MAC) and forwarding decision logic 22. For
20 purposes of this description, a port that acquires a data packet from an external entity such as a network, node, station, etc., for example, and forwards the packet internally to another port is referred to as an entry or sending port. A port that receives a data packet internally and transmits the data packet to an external entity is referred to as an exit or destination port. Also shown within the switch 18 is a
25 switch fabric 24 and a queuing device 26. Other portions of the switching device, which can be conventional in nature, are not shown and are not described because they are not germane to the invention.

The MAC and forwarding decision logic 22 within each port can be conventional in design. Through them a sending port acquires a data packet and
30 forwards it to one or more destination ports. The process for communicating forwarding decision is made by the forwarding decision logic based on destinations listed in the data packet. The forwarding decision logic 22 forwards to the queuing

00166343-100598
005007-2429160

device information (packet-related data) such as a pointer to where the packet is stored in the switch fabric (if the fabric is shared memory), the type of packet (priority, etc.) and to which ports the packet is to be communicated (one port for unicast, multiple ports for multicast, and all but the sending port for broadcast).

- 5 The forwarding decision logic also stores the data packet in the switch fabric 24 at the location indicated by the pointer.

The switch fabric 24 in the illustrative embodiment is a shared memory that stores the entire data packet and from which destination ports may retrieve a copy. However, the invention is not limited to shared memory architectures. The switch
10 fabric may be of other architectures such as a crossbar matrix.

The queuing device 26, which receives the packet-related data from the forwarding decision logic 22, is shown in more detail in Fig. 2. The device 26 includes characteristic detection logic 30, a first stage queue 32 coupled to the output of the detection logic, port membership determination logic 34 coupled to
15 the output of the first stage queue, and second stage logic 36 coupled to the output of the determination logic.

The characteristic detection logic 30 detects from the packet-related data a characteristic of the packet (e.g., priority) as well as determining from a destination list which ports are to retrieve the packet. The destination list in the
20 illustrative embodiment is encoded in the packet-related data as a number, which is used by the logic 30 to look up the associated port group in a look up table. Other means may also be used for indicating the destination ports, such as passing the port numbers directly within the packet-related data.

The first stage queue 32 stores the packet-related data according to a
25 characteristic of the packet. In the illustrative embodiment, that characteristic is the priority of the packet (from one to eight levels). Consequently the first stage queue includes multiple first queues, each one storing the packet-related data (pointer plus port group) for packets of a different priority level in the order in which they are received.

30 The port determination logic 34 reads the first stage queue according to a service scheme and determines from the packet-related data which destination ports

09466343 100593
B550T" CH99T60

are to receive the packet-related data in the first stage. The logic 34 then stores the pointers in the appropriate portion of the second stage queue 36.

The second stage queue 36 in the illustrative embodiment includes for each port connected to the queuing device a set of queues that correspond to the first stage queue. For example, the first stage queue includes eight priority queues, and the second stage queue includes for each of its connected ports a corresponding set of eight priority queues. With this arrangement, the pointers in each queue of the first stage queue can be easily copied into a corresponding queue in the second state queue for each determined destination port.

The queuing device also includes conventional logic (not shown in Fig. 2 for clarity) for requesting packets from the switch fabric 24 (packet req.) and for forwarding packets from the switch fabric to the destination ports (xmt packet). This conventional logic is included in the queuing device in the illustrative embodiment as an implementation choice. However, the logic could just as well be separate from the queuing device if desired.

Operation

A data packet communicated from a sending port of switch 18 to one or more destination ports travels through the switching device as follows. A data packet that is received by a port is processed by its MAC, which generates a well formed frame from the physical LAN interface. The MAC presents the packet to the forwarding decision logic 22 that classifies the packet type and makes a forwarding decision as to which ports the packet is to be sent to from a destination list within the packet. The forwarding decision logic 22 transfers the packet to a location in the switch fabric (shared memory in the illustrative embodiment). The forwarding decision logic 22 also generates the packet-related data which includes the type of packet, a pointer to the location in shared memory where the packet is stored, and the forward decision and sends this data to the queuing device 26.

The queuing device receives the packet-related data at detection logic 30 and stores it in the first stage queue 32. In the process of storing the data in the first stage queue the logic determines which from the data ports, if any, the packet should be queued for. The logic then stores the pointer and destination port

information in an appropriate queue within the first stage queue. In the illustrative embodiment the data is stored in a queue based on the priority of the packet; other characteristics of a packet can also be used for determining where the data will be stored.

5 The queuing device, through the determination logic 34, then obtains data from the multiple queues of the first stage in accordance with a scheme for reading the queues, such as a priority servicing scheme where the characteristic is priority. The determination logic 34 determines from the packet-related data just obtained which destination ports are to receive the pointer(s) and transfers the pointers to an
10 appropriate location in the second stage queue 36 associated with each determined destination port. In the illustrative embodiment the second stage queue includes multiple queues for each port that correspond to the multiple queues of the first stage queue. In this embodiment, with priority as the packet characteristic, the logic 36 transfers the pointers to the priority queue for each port corresponding to
15 the priority queue for the pointer in the first stage queue.

 The queuing device then uses the data in the second stage queue to complete the communication of the data packet from the sending port to each determined destination port. When servicing the second stage queue with a service scheme, the queuing device obtains pointers from the queues to packets in the
20 switch fabric 24 and requests these packets from the switch fabric. The switch fabric responds by sending the pointed-to packet to the queuing device, which then directs it to the appropriate port. Where there are multiple destination ports such in the case of a multicast data packet, the queuing device makes separate requests for each port.

25 The queuing device 26 is shown in the output or transmit path of the switch 18. In this configuration, the switch is said to be a "transmit buffered" or "output buffered" device. For different switch architectures like crossbar, the queuing device may reside on the inbound side of the switch, but the invention may still be applied. In that application, it would be referred to as "input buffered" since the
30 queues are stored at the sending ports of the switching device.

 Having understood the principles of the invention from the embodiments of the invention shown and described herein, those of skill in the art will recognize

005007 " 005007

that the embodiments can be modified in arrangement and detail without departing from such principles. The construction of the various modules can be varied while still providing the functions described. Elements of the various modules can be implemented in hardware, software, or firmware as desired. The packet-related

5 data may be pointers, other structures, or the data packets themselves. The invention may be used where appropriate in any packet switching device such as a LAN switch, a router, etc.

In view of the many possible embodiments to which the principles of the invention may be applied, it should be understood that these embodiments are

10 illustrative only and should not be taken as a limitation on the scope of the invention. The invention, rather, is defined by the following claims. We therefore claim as the invention all embodiments that may come within the scope of these claims and their equivalents.

0944 10050
" 463T60
06500T

We claim:

1. In a switching device, a method of communicating data packets from sending ports to destination device ports, the method comprising:
 - storing in a first stage queue packet-related data from a sending port;
 - 5 determining from the packet-related data which destination ports are to receive the packet-related data in the first stage queue;
 - storing in a second stage queue associated with each determined destination port the packet-related data from the first stage queue; and
 - using the packet-related data in the second stage queue to complete the
 - 10 communication of the data packet from the sending port to each determined destination port.
2. The method of claim 1 wherein the packet-related data is a pointer to memory and a list of destination ports.
3. The method of claim 1 including sending the packet-related data
- 15 from the sending port to the first stage queue.
4. The method of claim 1, wherein the first stage queue includes multiple first queues, and the step of storing the data in the first stage queue comprises storing the data in a specific first queue based on a characteristic of the packet.
- 20 5. The method of claim 1 wherein the packet characteristic is priority.
6. The method of claim 1 wherein the packet characteristic is network protocol type.
7. The method of claim 1 wherein the packet characteristic is type of service.
- 25 8. The method of claim 1 wherein the packet characteristic is other than whether the packet is a unicast or multicast type.
9. The method of claim 1 wherein each second stage queue includes multiple second queues, and the step of storing the data in the second stage queue comprises storing the data in a specific second queue based on a characteristic of
- 30 the packet.
10. The method of claim 1 wherein the packet-related data is a data packet.

0946349 100598
065007 " 463498

11. The method of claim 1 wherein the switching device uses a shared memory for communicating data packets from sending ports to destination ports, and the step of using the packet-related data in the second stage queue to complete the communication of the data packet from the sending port to each determined
5 destination port comprises using the data to obtain a copy of the data packet from the shared memory.

12. The method of claim 1 wherein the switching device uses a crossbar matrix for communicating data packets from sending ports to destination ports, and the step of using the packet-related data in the second stage queue to complete the
10 communication of the data packet from the sending port to each determined destination port comprises using the data to form connections in the matrix so as to communicate simultaneously a copy of the data packet from the sending port to each of the determined destination ports.

13. In a switching device, apparatus for communicating data packets
15 from sending ports to destination ports, comprising:
a first stage queue storing packet-related data from a sending port; and
a second stage queue associated with each of a set of destination ports storing the packet-related data from the first stage queue.

14. The apparatus of claim 13 including means for determining from the
20 packet-related data which destination ports are to receive the packet-related data in the first stage queue.

15. The apparatus of claim 14 including means for using the packet-related data in the second stage queue to complete the communication of the data packet from the sending port to each determined destination port.

25 16. The apparatus of claim 13 including address resolution logic sending the packet-related data from the sending port to the first stage queue.

17. The apparatus of claim 13 wherein the first stage queue includes multiple first queues, the data stored in a specific first queue based on a characteristic of the packet.

30 18. The apparatus of claim 13 wherein each second stage queue includes multiple second queues, the data stored in a specific second queue based on a characteristic of the packet.

09165343-100598

19. The apparatus of claim 13 wherein the switching device uses a shared memory for communicating data packets from sending ports to destination ports.

20. The apparatus of claim 13 wherein the switching device uses a
5 crossbar matrix for communicating data packets from sending ports to destination ports.

21. In a switching device, apparatus for communicating data packets from sending ports to destination ports, comprising:

means for storing in a first stage queue packet-related data from a sending
10 port;

means for determining from the packet-related data which destination ports are to receive the packet-related data in the first stage queue;

means for storing in a second stage queue associated with each determined destination port the packet-related data from the first stage queue; and

15 means for using the packet-related data in the second stage queue to complete the communication of the data packet from the sending port to each determined destination port.

09166343 "100598
00500T" 0429976

SWITCHING DEVICE WITH MULTISTAGE QUEUING SCHEME**ABSTRACT OF THE DISCLOSURE**

In a switching device, a method of communicating data packets from
5 sending ports to destination ports includes storing in a first stage queue packet-
related data from a sending port; determining from the packet-related data which
destination ports are to receive the packet-related data in the first stage queue;
storing in a second stage queue associated with each determined destination port
the packet-related data from the first stage queue; and using the packet-related data
10 in the second stage queue to complete the communication of the data packet from
the sending port to each determined destination port. Apparatus for practicing the
method comprises a first stage queue storing packet-related data from a sending
port; and a second stage queue associated with each of a set of destination ports
storing the packet-related data from the first stage queue.

15

09165343-100593




FIG. 1

2025001 24299150




Fig. 2

COMBINED DECLARATION AND POWER OF ATTORNEY FOR PATENT APPLICATION

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled **SWITCHING DEVICE WITH MULTISTAGE QUEUING SCHEME**, the specification of which

☒ is attached hereto.

☐ was filed on _____ as Application No. _____.

☐ was described and claimed in PCT International Application No. _____, filed on _____, and as amended under PCT Article 19 on _____ (if applicable).

☐ and was amended on _____ (if applicable).

☐ with amendments through _____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, § 1.56. If this is a continuation-in-part application filed under the conditions specified in 35 U.S.C. § 120 which discloses and claims subject matter in addition to that disclosed in the prior copending application, I further acknowledge the duty to disclose material information as defined in 37 CFR § 1.56 which occurred between the filing date of the prior application and the national or PCT international filing date of the continuation-in-part application.

I hereby claim foreign priority benefits under Title 35, United States Code, § 119(a)-(d) of any foreign application(s) for patent or inventor's certificate or of any PCT International application(s) designating at least one country other than the United States of America listed below and have also identified below any foreign application(s) for patent or inventor's certificate or any PCT International application(s) designating at least one country other than the United States of America filed by me on the same subject matter having a filing date before that of the application(s) on which priority is claimed:

Prior Foreign Application(s)

Priority
Claimed

_____	_____	_____	<input type="checkbox"/>	<input type="checkbox"/>
(Number)	(Country)	(Day/Month/Year Filed)	Yes	No

I hereby claim the benefit under Title 35, United States Code, § 119(e) of any United States provisional application(s) listed below:

_____	_____
(Application No.)	(Filing Date)

I hereby claim the benefit under Title 35, United States Code, § 120 of any United States application(s) or § 365(c) of any PCT International application(s) designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose material information as defined in Title 37, Code of

Federal Regulations, § 1.56(a) which occurred between the filing date of the prior application and the national or PCT International filing date of this application:

(Application No.)	(Filing Date)	(Status: patented, pending, abandoned)

The undersigned hereby authorizes the U.S. attorney or agent named herein to accept and follow instructions from _____ as to any action to be taken in the Patent and Trademark Office regarding this application without direct communication between the U.S. attorney or agent and the undersigned. In the event of a change in the persons from whom instructions may be taken, the U.S. attorney or agent named herein will be so notified by the undersigned.

I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application, to file a corresponding international application, and to transact all business in the Patent and Trademark Office connected therewith:

Name	Reg. No.	Name	Reg. No.
Kenneth S. Klarquist	16,445	Stacey C. Slater	36,011
James Campbell	19,978	Garth A. Winn	33,220
James S. Leigh	20,434	Stephen A. Wight	37,759
Arthur L. Whinston	19,155	Joel R. Meyer	37,677
David P. Petersen	28,106	Joseph T. Jakubek	34,190
Richard J. Polley	28,107	Robert F. Scotti	39,830
Ramon A. Klitzke II	30,188	Gregory V. Bean	36,448
William Y. Conwell	31,943	Lisa M. Caldwell	P41,653
Mark L. Becker	31,325	David J. Earp	41,401
William D. Noonan	30,878	Michael D. Jones	P41,879
John D. Vandenberg	31,312	Steven D. Yates	P42,242
John W. Stuart	24,540		
Donald L. Stephens Jr.	34,022		

Address all telephone calls to Mark L. Becker at telephone number (503) 226-7391.

Address all correspondence to:

KLARQUIST SPARKMAN CAMPBELL
LEIGH & WHINSTON, LLP
One World Trade Center, Suite 1600
121 S.W. Salmon Street
Portland, OR 97204-2988

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full name of third joint inventor, if any: C Stuart Johnson

Inventor's signature _____ Date

Residence: Liberty Lake, Washington

Citizenship: USA

Post Office address: 23815 E. Sinto, Liberty Lake, WA 99019

Full name of second joint inventor, if any: Greg W. Davis

Inventor's signature _____ Date

Residence: Spokane, Washington

Citizenship: USA

Post Office address: 3815 S. Union, Spokane, WA 99206

Full name of third joint inventor, if any: Timothy S. Michels

Inventor's signature _____ Date

Residence: Spokane, Washington

Citizenship: USA

Post Office address: 11621 E. 47th, Spokane, WA 99206

DECLARATION - PAGE 3 OF 3